

### CHALKWALL PAINT

|   |  |   |                        |
|---|--|---|------------------------|
| <b>TYPE OF MATERIAL</b>   | A blend of specially selected pigments and extenders in an aqueous Acrylic binder.   |   |                        |
| <b>USES</b>   | For creation of a Chalkwall area on walls or suitably primed boards. Can be used internally or externally.   |   |                        |
| <b>COLOURS AVAILABLE</b>  | Black.   |   |                        |
| <b>FINISH</b>   | Low Sheen.   | <b>TYPE REFERENCE NO.</b>                       | 880201, 880202, 880203 |
| <b>NUMBER OF COMPONENTS</b>                                     | one  | <b>MIXING RATIO</b>                             | N/A                    |
| <b>METHOD OF APPLICATION</b>                                    | Brush or Roller.   |   |                        |
| <b>PACK SIZES AVAILABLE</b>                                     | 500ML , 1Ltr & 2.5Ltr.   |   |                        |
| <b>VISCOSITY</b>  | 1.8-2.0 Poise at 20°C REL Cone & Plate.  |   |                        |
| <b>PRACTICAL COVERAGE PER LITRE</b>                             | 5 sq M/ltr depending on technique.   |   |                        |
| <b>WET FILM THICKNESS RANGE</b>                                 | N/A  |   |                        |
| <b>DRY FILM THICKNESS RANGE</b>                                 | N/A  |   |                        |
| <b>FLASH POINT</b>  | N/A  |   |                        |
| <b>DRYING TIMES:</b>  | <b>SURFACE</b>   | 2 hours   |                        |
|   | <b>HARD</b>  | 4-6 hours                                       |                        |
|   | <b>OVERCOATING</b>   | 6 hours, Leave for 24hrs before applying chalk. |                        |
| <b>CLEANING SOLVENT</b>   | Water.   |   |                        |
| <b>APPLICATION INSTRUCTIONS</b>                                 | Apply using normal application techniques. Do not overwork to avoid brushmarking. A minimum of two coats are required. Allow at least 24hrs before chalking.   |   |                        |
| <b>RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS</b> | Avoid applying in cold or damp conditions as this will delay drying, as will conditions of poor ventilation. Do not apply outside when temperature is below 5°C or when rain is likely. Allow at least 24hrs before chalking. If used externally a re-coat will be required after twelve months. |   |                        |
| <b>SAFETY PRECAUTIONS</b>                                       | Normal paint Health, Safety & Hygiene precautions apply. See tin label and Material Safety Data Sheet.   |   |                        |

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** CHALKWALL PAINT

**Product code:** 851

**Use / description of product:** For decorative use on walls, woodwork and other surfaces . See can label for more details.

**Company name:** Craig and Rose Ltd  
Unit 8, Halbeath Industrial Estate  
Crossgates Road  
Halbeath, Dunfermline  
Fife  
KY11 7EG  
Scotland  
Tel: +44 (0)1383 740 000  
Fax: +44 (0)1383 740 010  
Emergency tel: +44 (0)1383 740 000

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

## 3. HAZARDS IDENTIFICATION

**Main hazards:** No significant hazard.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvents or thinners.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

**Inhalation:** Consult a doctor. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**SAFETY DATA SHEET**

CHALKWALL PAINT

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid contact with skin and eyes. Prevent the generation of and inhalation of harmful dusts and fumes when preparing surfaces previously coated with lead containing paints. Further information is available from the British Coatings Federation ([www.coatings.org.uk](http://www.coatings.org.uk)).

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Store in original container or marked plastic container only.

**Storage quantity limits:** N/A

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Black

**Odour:** Perceptible odour

**Evaporation rate:** Moderate

**Solubility in water:** Soluble

**Also soluble in:** Ethanol.

**Viscosity:** Viscous

**Flammability limits %: lower:** N/A

**VOC g/l:** 2

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**SAFETY DATA SHEET**

CHALKWALL PAINT

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).

**Waste code number:** 08 01 11

**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** N/A

**IMDG / IMO**

**UN no:** N/A

**IATA / ICAO**

**UN no:** N/A

**15. REGULATORY INFORMATION**

**Hazard symbols:** No significant hazard.

**Precautionary phrases:** This product is classified as :  
category A/a

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## **SAFETY DATA SHEET**

CHALKWALL PAINT

### **16. OTHER INFORMATION**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.