

OIL SCUMBLE GLAZE

TYPE OF MATERIAL	A traditional oil based scumble glaze.		
USES	For all types of graining, stippling, dragging and other decorative paint finishes.		
COLOURS AVAILABLE	Clear. Can be tinted with most oil based paints, stainers or universal stainers.		
FINISH	Glossy	TYPE REFERENCE NO.	881158, 881159, 881160
NUMBER OF COMPONENTS	one	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush or other means.		
PACK SIZES AVAILABLE	500ML, 1Ltr & 2.5Ltr		
VISCOSITY	2.0-3.0 Poise at 20°C REL Cone & Plate.		
PRACTICAL COVERAGE PER LITRE	15-20 sq M/ Ltr depending on technique		
WET FILM THICKNESS RANGE	N/A		
DRY FILM THICKNESS RANGE	N/A		
FLASH POINT	40°C		
DRYING TIMES:	SURFACE	2-4 hours	
	HARD	16 hours	
	OVERCOATING	16-24 hours	
CLEANING SOLVENT	White Spirits		
APPLICATION INSTRUCTIONS	Glaze should be tinted to shade and then thinned to required consistency. This will depend on the technique used. In hot weather, the working time can be prolonged by adding a few drops of raw linseed oil, but great care should be taken not to add too much. The use of a little white paint will stabilise delicate colours		
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Avoid applying in cold or damp conditions as this will delay drying, as will conditions of poor ventilation. When the glaze is completely dry it should be overcoated with 1 coat of Craig & Rose Extra Pale Varnish.		
SAFETY PRECAUTIONS	Flammable. Normal paint Health, Safety & Hygiene precautions apply. See tin label and Material Safety Data Sheet.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: OIL SCUMBLE GLAZE

Product code: 831

Use / description of product: For Decoration and Protection of various internal and external surfaces. See can label for more details.

Company name: Craig and Rose Ltd
Unit 8, Halbeath Industrial Estate
Crossgates Road
Halbeath, Dunfermline
Fife
KY11 7EG
Scotland
Tel: +44 (0)1383 740 000
Fax: +44 (0)1383 740 010
Emergency tel: +44 (0)1383 740 000

2. COMPOSITION / INFORMATION ON INGREDIENTS

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be shortness of breath due to congestion of the lungs. Nausea and stomach pain may occur. There may be loss of consciousness. Convulsions may occur.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvents or thinners.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

SAFETY DATA SHEET

OIL SCUMBLE GLAZE

check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Contain the spillage using bunding. Do not discharge into drains or rivers. If this product enters drains, sewers, rivers or other waters, inform the water company and / or relevant environmental agency immediately.

Clean-up procedures: Absorb into dry earth or sand. Collect in a suitable metal container and dispose of in accordance with the waste regulations (see section 7). Clean area, preferably with a detergent. Do not use solvents.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: All equipment including engineering controls and personal protective equipment, used to control exposure to dangerous substances must be selected to meet the requirements of the COSHH regulations.

Respiratory protection: If spraying, wear a suitable mask or respirator. Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Seek advice from the glove supplier to ensure that the correct type of glove is selected and follow their advice on the storage, maintenance and replacement of the gloves. Barrier creams may help to protect exposed areas of skin, but are no substitute for full physical protection. They must be applied before exposure occurs.

Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Remove all contaminated clothes and footwear immediately. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Always wash your hands before eating, drinking, smoking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES**State:** Liquid**Colour:** Off-white**Odour:** Characteristic odour**Oxidising:** Non-oxidising (by EC criteria)**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Viscosity value:** >150secs**Viscosity test method:** Flow time in seconds in a 3 mm ISO cup (ISO 2431)**Flammability limits %: lower:** 0.8**Flash point°C:** 40**VOC g/l:** 400**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Sources of ignition. Direct sunlight.**Materials to avoid:** Oxidising agents. Strong acids. Strong bases.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Chronic toxicity:** No data is available on this product. Splashes to the eye may cause irritation and reversible local damage**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Insoluble in water.**Persistence and degradability:** No data available.**Bioaccumulative potential:** No data available.**Other adverse effects:** Very toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.). Via an authorised waste disposal contractor, according to local or national regulations.
Some local authorities have special schemes for the re-use of part full paint containers.**Waste code number:** 08 01 011**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET

OIL SCUMBLE GLAZE

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1263 **ADR Class:** 3
Packing group: III
Shipping name: PAINT
Hazard ID no: 30

IMDG / IMO

UN no: 1263 **Class:** 3
Packing group: III **EmS:** 3-05
Marine pollutant: YES **Labelling:** 3

IATA / ICAO

UN no: 1263 **Class:** 3
Packing group: III **Packing instructions:** 310
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.



Risk phrases: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains cobalt carboxylate, zirconium carboxylate. May produce an allergic reaction.

This product is classified as :

category A/1

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.