

SAFETY DATA SHEET

1 IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT NAME AND/OR CODE: **Predec Stains and Primers- Incuding** **Stains**
Light/Premium 20D78
Medium/Standard 20D77
RSG 50D90
Primers
white 35B2

INTENDED USE: **Penetrating Basecoats and primers for exterior joinery.**

NAME & FULL ADDRESS: **Arch Coatings UK Ltd**
A1 Business Park
KNOTTINGLEY
West Yorkshire
WF11 0BU

TELEPHONE NO: **01977 673363**

EMERGENCY NO: **01977 673521 (fax)**

2 COMPOSITION/INFORMATION OF INGREDIENTS

Substances presenting a health hazard within the meaning of the CHIP Regulations or assigned occupational exposure limits.

Substance	Conc Range %	Symbol Letter	R Phrases ⁽⁵⁾	Occupational Exposure Limits				Notations ⁽³⁾
				8 hr TWA ⁽¹⁾		15 min STEL ⁽²⁾		
				ppm ⁽⁴⁾	mg/m ³⁽⁴⁾	ppm ⁽⁴⁾	mg/m ³⁽⁴⁾	
White Spirit	75-100	Xn	10, 65	95 SUP	550 SUP	-	-	
Glycol ether	1-2.5	Xi	36	(6)	(6)	(6)	(6)	

Notes:

- (1) Long term exposure limit – 8 hour time weighted average.
- (2) Short term exposure limit – 15 minute reference period.
- (3) 'Sk' indicates a risk of absorption through the skin. 'Sen' indicates a respiratory sensitiser.
- (4) 'OES' indicates an Occupation Exposure Standard. 'MEL' indicates a Maximum Exposure Limit.
'OEL's' are taken from EH40, except those marked 'SUP', which are assigned by the supplier of the substance.
'Bmgv' indicates that biological monitoring may be appropriate. Biological Monitoring Guidance Values are listed in EH40.
- (5) For full text see Section 15.
- (6) Values have not been assigned by the supplier.

3 HAZARDS IDENTIFICATION

The product is classified as flammable and harmful according to the CHIP Regulations.
Harmful may cause lung damage if swallowed
Flammable.

4 FIRST AID MEASURES

General:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recover position and seek medical advice.

Eye Contact:

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding eyelids apart and seek medical advice.

Skin Contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner.
DO NOT USE SOLVENTS OR THINNERS.

Ingestion:

If accidentally swallowed obtain immediate medical attention and show this handling safety data sheet or the can label. Keep at rest. Do NOT induce vomiting.

5 FIRE FIGHTING MEASURES

Extinguishing Media:

RECOMMENDED: Alcohol resistant foam, CO₂ powder, water spray/mist
NOT TO BE USED: Water jet

Recommendations:

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

6 ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent and avoid the use of solvents.

If the product enters drains or sewers the local Water Company should be contacted immediately; in case of contamination of streams, rivers or lakes, the relevant environment agency.

7 HANDLING AND STORAGE

Handling:

Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

Additionally, the product should only be used in areas which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection see Section 8.

Unless the container is specifically designed, never use pressure to empty. It is not a pressure vessel.

Always keep in containers made of the same material as the supply container.

Good housekeeping standards including the regular safe removal of waste materials and regular maintenance of spray booth filters will minimise risks of spontaneous combustion and other fire hazards.

The Manual Handling Operations Regulations may apply to the handling of containers of the product. Refer to the guide weight indicated on the container when carrying out assessments.

Storage:

Observe the label precautions.

Store between 5 and 25°C in a dry, well-ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers that are opened should be properly resealed and kept upright to prevent leakage.

The principles contained in the HSE's guidance note Storage of Flammable Liquids in Containers should be observed when storing this product.

Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

(see Section 2).

Engineering Measures:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupation exposure limits, suitable respiratory protective equipment should be worn (see Personal Protection below).

Personal Protection:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Respiratory Protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupation exposure limit and engineering controls and methods cannot reasonably be improved.

Hand Protection:

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of the skin, but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

Eye Protection:

Eye protection designed to protect against liquid splashes should be worn.

Skin Protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

DO NOT USE SOLVENTS OR THINNERS AS SKIN CLEANING AGENTS.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid	
Flash Point:	39-42°C	Method: Abel closed cup
Viscosity:	26 Sec	Method: DIN 3 at 23°C
Specific Gravity:	0.82-0.89	Method: weight of 100 ml at 20°C
Vapour Density:	Heavier than air	
Lower Explosion Limit:	Not determined	
Solubility in Water:	Immiscible	

10**STABILITY AND REACTIVITY**

Stable under the recommended storage and handling conditions (see Section 7). In a fire, hazardous decomposition products such as smoke, carbon monoxide and carbon dioxide and oxides of nitrogen may be produced.
Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.
Keep dirty wipers in an enclosed container.

11**TOXICOLOGICAL INFORMATION**

There is no data available on the product itself. Exposure to organic solvent vapours may result in adverse health effects, such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage. Ingestion may result in the following effects: sore throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea. Other effects may be as described for exposure to vapours.

12**ECOLOGICAL INFORMATION**

There is no data available on the product itself. The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product .

13**DISPOSAL CONSIDERATIONS**

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using the information provided in this safety data sheet, advice should be obtained from the relevant environment agency, whether the special waste regulations apply.

14**TRANSPORT INFORMATION****Transport within the user's premises:**

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

Transport Details:

CLASS 3 - PACKING GROUP 3

Ensure drivers have adequate training.

The product is classified and labelled for supply in accordance with the CHIP Regulations (except those marked *, for information only).

R No	Phrase
R10	FLAMMABLE
R65	HARMFUL, MAY CAUSE LUNG DAMAGE IF SWALLOWED
R36*	IRRITATING TO EYES
S No	Phrase
S2	KEEP OUT OF REACH OF CHILDREN
S16	KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING
S23	DO NOT BREATHE VAPOURS OR SPRAY
S24/25	AVOID CONTACT WITH SKIN AND EYES
S28	AFTER CONTACT WITH SKIN, WASH IMMEDIATELY WITH PLENTY OF SOAP AND WATER
S51	USE ONLY IN WELL VENTILATED AREAS
S62	IF SWALLOWED, DO NOT INDUCE VOMITING: SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER AND LABEL

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

The information contained in this safety data sheet is provided in accordance with the requirements of CHIP Regulations.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in the following:

The Control of Substances Hazardous to Health Regulations 1999 (SI 1999: 437)
 (Control of Substances Hazardous to Health Regulations (NI) 1995)
 The Manual Handling Operations Regulations 1992 (SI 1992: 2793)
 Storage of Flammable Liquids in Containers, HS(G)51
 Storage of Packaged Dangerous Substances, HS(G)71
 The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992: 2839)
 EH40/## Occupational Exposure Limits, HSE Books
 A Guide to Working with Solvents, INDG 272