

ACRYLIC VARNISH, GLOSS, EGGSHELL & FLAT

TYPE OF MATERIAL	A hard wearing clear varnish based on pure Acrylic resins.		
USES	This varnish is quick drying and does not yellow. For use over wood & painted finishes.		
COLOURS AVAILABLE	Clear.		
FINISH	Gloss, Eggshell & Flat.	TYPE REFERENCE NO.	880100, 880108
NUMBER OF COMPONENTS	one	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush or Roller.		
PACK SIZES AVAILABLE	500ML, 1Ltr & 2.5Ltr		
VISCOSITY	0.2-0.4 Poise at 20°C REL Cone & Plate.		
PRACTICAL COVERAGE PER LITRE	15sq M/ Ltr.		
WET FILM THICKNESS RANGE	Variable on porous surfaces.		
DRY FILM THICKNESS RANGE	Variable on porous surfaces.		
FLASH POINT	N/A		
DRYING TIMES:	SURFACE	30 mins	
	HARD	2 hours	
	OVERCOATING	2-4 hours	
CLEANING SOLVENT	Water.		
APPLICATION INSTRUCTIONS	Apply normally by brush, roller or airless spray. Special brushes for water paints are available and will give better finish. Stir or shake contents well before use to ensure an even finish. Always test a small area for suitability before applying. This is particularly important for dark colours. If using the Acrylic Flat Varnish, seal very porous surfaces first with an eggshell or gloss varnish. Ensure that Flat varnish is thoroughly mixed before using.		
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Do not apply in cold or damp conditions as this may retard drying and film formation. Do not store the varnish where it may freeze. Do not use over oil scumble glaze without checking a small area for colour stability. Do not use on floors subject to heavy traffic.		
SAFETY PRECAUTIONS	Normal paint Health, Safety & Hygiene precautions apply. See tin label and Material Safety Data Sheet.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ACRYLIC VARNISH

Product code: 835

Synonyms: ACRYLIC GLOSS VARNISH
ACRYLIC EGGSHELL VARNISH
ACRYLIC FLAT VARNISH

Use / description of product: For decorative use on walls, woodwork and other surfaces . See can label for more details.

Company name: Craig and Rose Ltd
Unit 8, Halbeath Industrial Estate
Crossgates Road
Halbeath, Dunfermline
Fife
KY11 7EG
Scotland
Tel: +44 (0)1383 740 000
Fax: +44 (0)1383 740 010
Emergency tel: +44 (0)1383 740 000

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: TEXANOL (IBP 255°C) 1-10%
EINECS: 246-771-9 CAS: 25265-77-4
[-] R52

- AMMONIA 0 88 30% <1%
EINECS: 215-647-6 CAS: 1336-21-6
[C] R34; [N] R50

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvents or thinners.

SAFETY DATA SHEET

ACRYLIC VARNISH

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid contact with skin and eyes. Prevent the generation of and inhalation of harmful dusts and fumes when preparing surfaces previously coated with lead containing paints. Further information is available from the British Coatings Federation (www.coatings.org.uk).

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Store in original container or marked plastic container only.

Storage quantity limits: n/a

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Respiratory protection not required. If spraying, wear a suitable mask or respirator.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing. Always wash your hands before eating, drinking, smoking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Translucent White effect.

Odour: Perceptible odour

Evaporation rate: Moderate

SAFETY DATA SHEET

ACRYLIC VARNISH

Solubility in water: Soluble**Also soluble in:** Ethanol.**Viscosity:** Viscous**Flammability limits %: lower:** N/A**Flash point°C:** N/A**Autoflammability°C:** N/A**VOC g/l:** 3**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).**Waste code number:** 08 01 12**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** N/A**Shipping name:** (This product is not classed as dangerous for carriage)**IMDG / IMO****UN no:** N/A**Labelling:** This product is not classed as dangerous

SAFETY DATA SHEET

ACRYLIC VARNISH

IATA / ICAO

UN no: N/A

Labelling: This product is not classed as dangerous for carriage

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Precautionary phrases: This product is classified as :

category A/e

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle

Refinishing products regulations, SI 2005: 2773.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R52: Harmful to aquatic organisms.

R34: Causes burns.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.