

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** PLASTER PRIMER SEALER

**Product code:** 801

**Synonyms:** ACRYLIC PRIMER SEALER

PLASTER PRIMER SEALER

**Use / description of product:** For use on internal walls and ceilings.

**Company name:** Craig and Rose Ltd

Unit 8, Halbeath Industrial Estate

Crossgates Road

Halbeath, Dunfermline

Fife

KY11 7EG

Scotland

Tel: +44 (0)1383 740 000

Fax: +44 (0)1383 740 010

Emergency tel: +44 (0)1383 740 000

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** AMMONIA 0 88 30% <1%

EINECS: 215-647-6 CAS: 1336-21-6

[C] R34; [N] R50

## 3. HAZARDS IDENTIFICATION

**Main hazards:** No significant hazard.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvents or thinners.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

**SAFETY DATA SHEET**

PLASTER PRIMER SEALER

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid contact with skin and eyes. Prevent the generation of and inhalation of harmful dusts and fumes when preparing surfaces previously coated with lead containing paints. Further information is available from the British Coatings Federation ([www.coatings.org.uk](http://www.coatings.org.uk)).

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Store in original container or marked plastic container only.

**Storage quantity limits:** n/a

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** AMMONIA 0 88 30%  
WEL (8 hr exposure limit): 25 ppm

**Respiratory protection:** Respiratory protection not required. If spraying, wear a suitable mask or respirator.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing. Always wash your hands before eating, drinking, smoking or using the toilet.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** White

**Odour:** Perceptible odour

**Evaporation rate:** Moderate

**Solubility in water:** Soluble

**Also soluble in:** Ethanol.

**SAFETY DATA SHEET**

PLASTER PRIMER SEALER

**Viscosity:** Viscous

**Flammability limits %: lower:** n/a

**Flash point°C:** n/a

**Autoflammability°C:** n/a

**VOC g/l:** 30

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).

**Waste code number:** 08 01 12

**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION**

**ADR / RID**

**UN no:** n/a

**IMDG / IMO**

**UN no:** n/a

**IATA / ICAO**

**UN no:** n/a

**15. REGULATORY INFORMATION**

**Hazard symbols:** No significant hazard.

**Precautionary phrases:** This product is classified as :

**SAFETY DATA SHEET**  
PLASTER PRIMER SEALER

category A/g

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Risk phrases used in s.2:** R34: Causes burns.

R50: Very toxic to aquatic organisms.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.