



TDS 801 APS V2

TECHNICAL DATA SHEET

801

ACRYLIC PRIMER / SEALER

TYPE OF MATERIAL	A water based acrylic emulsion sealer, for use on plaster surfaces.		
USES	A quick drying sealer for dry or powdery plaster surfaces which require sealing before painting. For use on plaster walls or ceilings.		
COLOURS AVAILABLE	White		
FINISH	Low Sheen.	TYPE REFERENCE NO.	880155,880156,880200
NUMBER OF COMPONENTS	one	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush, Roller or as required.		
PACK SIZES AVAILABLE	1Ltr, 2.5Ltr & 5Ltr.		
VISCOSITY	0.6-1.0 Poise at 20°C REL Cone & Plate.		
PRACTICAL COVERAGE PER LITRE	12-14 sq M / Ltr depending on porosity.		
WET FILM THICKNESS RANGE	N/A		
DRY FILM THICKNESS RANGE	N/A		
FLASH POINT	N/A		
DRYING TIMES:	SURFACE	1 hour	
	HARD	2 hours	
	OVERCOATING	2-4 hours.	
CLEANING SOLVENT	Water.		
APPLICATION INSTRUCTIONS	Apply by brush, roller or spray.		
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Avoid applying in cold or damp conditions as this will slow the Surfaces must be clean, dry and grease free. Store in a frost free area. Do not thin out as this will reduce the binding capacity of the sealer.		
SAFETY PRECAUTIONS	Normal paint Health, Safety & Hygiene precautions apply. See tin label and Material Safety Data Sheet.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PLASTER PRIMER SEALER

Product code: 801

Synonyms: ACRYLIC PRIMER SEALER
PLASTER PRIMER SEALER

Use / description of product: For use on internal walls and ceilings.

Company name: Craig and Rose Ltd
Unit 8, Halbeath Industrial Estate
Crossgates Road
Halbeath, Dunfermline
Fife
KY11 7EG
Scotland
Tel: +44 (0)1383 740 000
Fax: +44 (0)1383 740 010
Emergency tel: +44 (0)1383 740 000

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: AMMONIA 0 88 30% <1%
EINECS: 215-647-6 CAS: 1336-21-6
[C] R34; [N] R50

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvents or thinners.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

SAFETY DATA SHEET

PLASTER PRIMER SEALER

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid contact with skin and eyes. Prevent the generation of and inhalation of harmful dusts and fumes when preparing surfaces previously coated with lead containing paints. Further information is available from the British Coatings Federation (www.coatings.org.uk).

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Store in original container or marked plastic container only.

Storage quantity limits: n/a

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: AMMONIA 0 88 30%
WEL (8 hr exposure limit): 25 ppm

Respiratory protection: Respiratory protection not required. If spraying, wear a suitable mask or respirator.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing. Always wash your hands before eating, drinking, smoking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: White

Odour: Perceptible odour

Evaporation rate: Moderate

Solubility in water: Soluble

Also soluble in: Ethanol.

SAFETY DATA SHEET

PLASTER PRIMER SEALER

Viscosity: Viscous**Flammability limits %: lower:** n/a**Flash point°C:** n/a**Autoflammability°C:** n/a**VOC g/l:** 30**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).**Waste code number:** 08 01 12**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** n/a**IMDG / IMO****UN no:** n/a**IATA / ICAO****UN no:** n/a**15. REGULATORY INFORMATION****Hazard symbols:** No significant hazard.**Precautionary phrases:** This product is classified as :

SAFETY DATA SHEET
PLASTER PRIMER SEALER

category A/g

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R34: Causes burns.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.