

SUPEROSE WOOD PRIMER

TYPE OF MATERIAL	An oil based wood primer utilising Non lead pigments and extenders in a linseed oil/alkyd blend.		
USES	A high quality lead free wood primer for internal and external use.		
COLOURS AVAILABLE	White		
FINISH	Low sheen	TYPE REFERENCE NO.	881133, 881134,881135
NUMBER OF COMPONENTS	one	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush		
PACK SIZES AVAILABLE	1Ltr, 2.5Ltr & 5Ltr		
VISCOSITY	3.0-3.5 Poise at 20°C REL Cone & Plate.		
PRACTICAL COVERAGE PER LITRE	8-10 sq M/ Ltr depending on porosity.		
WET FILM THICKNESS RANGE	N/A		
DRY FILM THICKNESS RANGE	Approx 35 microns		
FLASH POINT	42°C		
DRYING TIMES:	SURFACE	3-5 hours	
	HARD	16 hours	
	OVERCOATING	16-24 hours	
CLEANING SOLVENT	White Spirits		
APPLICATION INSTRUCTIONS	For best performance apply by brush. Brush well into the wood surface to displace air and make good contact. Do not apply too heavy a coat. On very dry or weathered wood a second coat may be necessary.		
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Do not apply in cold or damp conditions as this will retard drying and over-coating times. Do not apply if the moisture content of the timber is above 18%.		
SAFETY PRECAUTIONS	Flammable. Normal paint Health, Safety & Hygiene precautions apply. See tin label and Material Safety Data Sheet.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SUPEROSE WOOD PRIMER

Product code: 804

Synonyms: WOOD PRIMER

Use / description of product: Primer for Internal and External use on Woodwork and other Joinery surfaces.

Company name: Craig and Rose Ltd
Unit 8, Halbeath Industrial Estate
Crossgates Road
Halbeath, Dunfermline
Fife
KY11 7EG
Scotland
Tel: +44 (0)1383 740 000
Fax: +44 (0)1383 740 010
Emergency tel: +44 (0)1383 740 000

2. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** WHITE SPIRIT BS245 10-30%
EINECS: 265-185-4 CAS: 64742-82-1
[-] R10; [N] R51/53; [Xn] R65; [Xi] R66
- DE-AROMATISED KEROSENE 1-10%
EINECS: 265-150-3 CAS: 64742-48-9
[Xn] R65; [Xi] R66

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

SAFETY DATA SHEET

SUPEROSE WOOD PRIMER

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

Storage quantity limits: n/a

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: WHITE SPIRIT BS245
WEL (8 hr exposure limit): 600 mg/m³ WEL (15 min exposure limit): 3200 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: White

SAFETY DATA SHEET

SUPEROSE WOOD PRIMER

Odour: Characteristic odour**Evaporation rate:** Fast**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Flash point°C:** 42**VOC g/l:** 310**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).

R1 Solvent reclamation/regeneration.

Waste code number: 08 01 11**Disposal of packaging:** Nominally empty containers where contents have dried out fully can be disposed of with normal waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1263**ADR Class:** 3**Packing group:** III**Shipping name:** PAINT**IMDG / IMO****UN no:** 1263**Class:** 3

SAFETY DATA SHEET

SUPEROSE WOOD PRIMER

Packing group: III**EmS:** F-E,S-E**Labelling:** PAINT PRODUCT**IATA / ICAO****UN no:** 1263**Class:** 3**Packing group:** III**Labelling:** PAINT PRODUCT**15. REGULATORY INFORMATION****Hazard symbols:** Symbol not required.**Risk phrases:** R10: Flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S29: Do not empty into drains.

Precautionary phrases: Contains ethyl methyl ketoxime, cobalt carboxylate, zirconium carboxylate. May produce an allergic reaction.

This product is classified as :

category A/g

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Risk phrases used in s.2:** R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.